




Domino Symphony PCIe

Frame grabber for four single-tap non-standard analog cameras



At a Glance

- Four 10-bit 65 MHz A/D converters with four 8- or 10-bit LUTs
- PCIe x1 bus
- D³ technology for extremely low synchronization jitter
- Support for mega-pixel progressive-scan and interlaced cameras, asynchronous reset and exposure control
- Trigger, strobe and general purpose I/O lines

Benefits

Enjoy digital quality from low-cost analog cameras thanks to our patented D³ technology

- Extremely low noise, true 10-bit image acquisition
- Lowest jitter: 0.5 ns (or 0.008 pixels) even when using composite video signals, for the most precise measurements
- No need to use pixel clock

Take advantage of the lowest-cost industrial cameras available on the market

Windows drivers available

Applications

Machine Vision for the General Manufacturing Industries

- Low cost image acquisition from industrial analog cameras for inspection machines

Specifications

Mechanical

Form Factor	PCI Express card
Format	Standard profile, half length, 1-lane PCI Express card
Dimensions	L 167.65 mm x H 111.15 mm L 6.6 in x H 4.38 in
Weight	135 g, 4.76 oz

Host bus

Standard	PCI Express 1.0
Link width	1 lane
Link speed	2.5 GT/s (PCIe 1.0)
DMA	32-bit
Peak delivery bandwidth	256 MB/s
Effective (sustained) delivery bandwidth	180 MB/s (Host PC motherboard dependent)
Power consumption	Typ. 8.3 W (940 mA @ +3.3V, 430 mA @ +12V), excluding I/O power output

Camera / video inputs

Interface standard(s)	Non-standard Analog
Connectors	<ul style="list-style-type: none">• CAMERAS: high-density sub-D 44-pin male connector for video and camera control• Internal video: 10-pin shrouded header video connector on the PCB
Termination resistor	Selectable by software
Number of cameras	Four single-tap cameras
Number of cameras (at full frame rate)	4
Line-scan cameras supported	No
A/D converter	Four, 10-bit, 65 MHz
Maximum camera line rate	52.5 kHz

On-board processing

On-board memory	64 MB (32 MB for image data)
Input LUT (Lookup Table)	4 x 8- or 10-bit LUT

General Purpose Inputs and Outputs

Number of lines	32 I/O lines: <ul style="list-style-type: none">• 4 contact inputs (Factory I/O: IN)• 12 relay outputs (Factory I/O: OUT)• 4 TTL inputs/outputs (System: IO)• 4 differential inputs (System: TR)• 4 opto-isolated outputs (System: ST)• 4 full-duplex serial com ports (Camera COM: RX/TX)
Connectors	<ul style="list-style-type: none">• EXTERNAL SYSTEM: 26-pin high-density male sub-D connector on the bracket• INTERNAL SYSTEM: 26-pin dual-row 0.1" shrouded header on the PCB• FACTORY I/O: 34-pin dual-row 0.1" shrouded header on the PCB• CAMERA COM: 16-pin dual-row 0.1" shrouded header on the PCB• Molex 4-pin connector on the PCB for powering cameras
Usage	<ul style="list-style-type: none">• Camera and image acquisition trigger• Light strobe trigger• General purpose IO

Electrical specifications

- TR: Inputs compatible with TTL, LVTTTL, differential LVDS, differential RS-422, differential RS-485 signals, protected against electrostatic discharge, with choke for the rejection of common-mode noise
- ST: Opto-isolated outputs, compatible with signals up to 60V, with 3 μ s fall time, isolated up to 500V
- IO: Inputs or outputs compatible with TTL signals, protected against electrostatic discharge, with high-frequency noise filter
- IN: Polarity-free inputs, compatible with TTL, 12V and 24V signals, opto-couplers, relays and switches
- OUT: Opto-isolated potential-free and polarity-free solid-state outputs, compatible with signals up to 30V, with 4 μ s fall time, isolated up to 500V
- COM: RS232 asynchronous serial communication lines to control the cameras (exposed to the OS as standard COM ports)

Software

Host PC Operating System

- Microsoft Windows 10, 8.1, 7 for x86 (32-bit) and x86-64 (64-bit) processor architectures
- Linux for x86 (32-bit) and x86-64 (64-bit) processor architectures

Refer to release notes for details

APIs

- MultiCam 32- and 64-bit binary libraries (Windows and Linux), for ISO-compliant C/C++ compilers

Environmental conditions

Operating ambient air temperature	0 to +50 °C / +32 to +122 °F
-----------------------------------	------------------------------

Operating ambient air humidity	10 to 90% RH non-condensing
--------------------------------	-----------------------------

Storage ambient air temperature	-20 to +70 °C / -4 to +158 °F
---------------------------------	-------------------------------

Storage ambient air humidity	10 to 90% RH non-condensing
------------------------------	-----------------------------

Certifications

Electromagnetic - EMC standards	• European Council EMC Directive 2004/108/EC
---------------------------------	--

EMC - Emission	• EN 55022:2010 Class B
----------------	-------------------------

EMC - Immunity	• EN 55024:2010 Class B
----------------	-------------------------

KC Certification	Korean Radio Waves Act, Article 58-2, Clause 3
------------------	--

Flammability	PCB compliant with UL 94 V-0
--------------	------------------------------

RoHS	European Union Directive 2011/65/EU (ROHS2)
------	---

REACH	European Union Regulation 1907/2006
-------	-------------------------------------

WEEE	Must be disposed of separately from normal household waste and must be recycled according to local regulations
------	--

Ordering Information

Product code - Description	• 1601 - Domino Symphony PCIe
----------------------------	-------------------------------

Optional accessories	6011 - Symphony Spider Cable
----------------------	------------------------------



AMERICA

Euresys Inc.

27126-B Paseo Espada - Suite 704
San Juan Capistrano, CA 92675 - United States

Phone: +1 949 743 0612

Email: sales.americas@euresys.com

EMEA

Euresys SA

Liège Science Park - Avenue du Pré Aily, 14
4031 Angleur - Belgium

Phone: +32 4 367 72 88

Email: sales.europe@euresys.com

EMEA

Sensor to Image GmbH

Lechtorstrasse 20 -
86956 Schongau - Germany

Phone: +49 8861 2369 0

Email: sales.europe@euresys.com

ASIA

Euresys Pte. Ltd.

750A Chai Chee Road - #07-15 Viva Business Park
Singapore 469001 - Singapore

Phone: +65 6445 4800

Email: sales.asia@euresys.com

CHINA

Euresys Shanghai Liaison Office

Unit 802, Tower B, Greenland The Center - No.500 Yunjin Road, Xuhui District
200232 Shanghai - China

Euresys上海联络处

上海市徐汇区云锦路500号绿地汇中心B座802室
200232

Phone: +86 21 33686220

Email: sales.china@euresys.com

JAPAN

Euresys Japan K.K.

Expert Office Shinyokohama - Nisso Dai 18 Building, Shinyokohama 3-7-18
Kouhoku-Ku, Yokohama-Shi 222-0033 - Japan

〒222-0033

神奈川県横浜市港北区新横浜3-7-18 日総第18ビル エキスパートオフィス新横浜

Phone: +81 45 594 7259

Email: sales.japan@euresys.com

More at www.euresys.com

